

FOUND BLM MONUMENT AT QUARTER CORNER

POSITION OF 1/16 CORNER DETERMINED BY SINGLE PROPORTION BASED ON 1882 G.L.O. SURVEY DATA (NOT SET)
S 88°46'38" E 2631.59'

FOUND COUNTY MONUMENT AS PER COUNTY SURVEY MONUMENT RECORD

FOUND G.L.O. 1922 BRASS CAP AT 1/4 CORNER


N 88°46'38" W 1297.11'

667.24'

1334.48'

667.24'

N 89°49'27" E 2642.85'



SCALE: 1=200'



LEGEND AND NOTES

- 5/8"X24" REBAR WITH CAP STAMPED 148951 SET BY THIS SURVEY
- FOUND 1/2" REBAR

THIS SURVEY WAS PERFORMED USING GLOBAL POSITIONING SYSTEM (G.P.S.) EQUIPMENT AND PROCEDURES. BEARINGS ARE BASED ON WGS84 DATUM.

FOUND BLM MONUMENT AT 1/16 CORNER

N 89°31'35" W 1310.43'

FOUND 1/2" REBAR AT 1882 G.L.O. SURVEY POSITION--SET COUNTY MONUMENT

400.00'

667.51'

267.51'
S 89°34'30" E 1335.03'

667.51'

FOUND 5/8" REBAR AT 1/16 CORNER

N 00°05'13" W 1322.43'

N 00°15'29" W 1321.61'

660.81'

LATH SET ALONG PROPERTY LINE

1053.79'
N 89°34'10" W 1328.99'

275.20'

S 00°44'34" E 1287.22'

343.57'

1321.78'

S 00°15'00" W 1321.78'

660.89'

660.89'

FOUND COUNTY MONUMENT AS PER COUNTY SURVEY MONUMENT RECORD

SEC 25 SEC 30

N 89°33'50" W 1314.38'

SEC 36 SEC 31

S 89°33'50" E 2637.34'


FOUND 5/8" REBAR AT 1/16 CORNER

S 89°33'50" E 1322.96'

POSITION OF 1/4 CORNER DETERMINED ON PREVIOUS SURVEY USING OLD FENCE LINE EVIDENCE

PROPERTY SURVEY FOR DUCHESNE COUNTY SECTION 30, TOWNSHIP 3 SOUTH, RANGE 2 WEST UINTAH SPECIAL BASE & MERIDIAN

SECTION 30, T3S, R2W U.S.B.&M.



THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT LOCATED AT LAT. 40°12'52.40875"N AND LONG. 110°11'03.67701"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER

NARRATIVE

This survey was performed at the request of the Duchesne County Road Department for the purpose of marking the boundaries of parcel owned by the County in Section 30 shown on this plat.


Section 30 was originally surveyed by the General Land Office in 1882 using the "3-mile method". The boundary and parts of the interior were later resurveyed by the G.L.O. in 1922, again using the "3-mile method".

A search was made for the monuments marking the Public Land Survey System (PLSS) corners and the results are noted on the plat. These found corners were used to control the survey.

This plat represents the dependent resurvey and the Three Mile Method subdivision of a portion of Section 30, and is designed to restore the PLSS corners to their true original location according to the best available evidence. The basis of bearings for the survey is geodetic north derived from G.P.S. observations using the Utah State G.P.S. Virtual Reference Station control network maintained and operated by the Automated Geographic Reference Center.


SURVEYOR'S CERTIFICATE

This is to certify that this plat was prepared from the field notes and electronic data collector files of an actual survey made by me, or under my personal supervision, of the parcel of land shown hereon, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.



Jerry D. Allred, Professional Land Surveyor, Certificate No. 148951, (Utah)

County Surveyor's File # 2183



JERRY D. ALLRED AND ASSOCIATES

SURVEYING CONSULTANTS

1235 NORTH 700 EAST--P.O. BOX 975
DUCHESNE, UTAH 84021
(435) 738-5352